



PINENTALERT

Entry Alert System



Features

- For monitoring an entrance or use as an entrance indicator
- Retroreflective beam sensor
- Range: Up to 22ft (7m)
- Makes “dingdong” or siren sound if beam is interrupted
- Speaker volume can be adjusted or turned off. In siren mode, sounding time adjustable from 3 to 30 seconds
- 9VDC adapter included
- All components plug into each other. No hard wiring required

Includes the following

- Retroreflective photoelectric sensor
- Reflector
- Speaker/electronic chime
- 9VDC 200mA power adapter
- Mounting brackets for sensor, reflector and chime
- Optional Accessories: Additional Speaker (PINENTSPEAK) and Counter (PINENTCOUNT)

Specifications

Part Number	PINENTALERT
Type	RetroReflective
Sensing Range	22' (7m)
Supply Voltage	9 - 15VDC
Total Current Consumption	100mA Max.
Standby	current 30mA
Light Source	IR LED
Ambient Temp	20°C ~ 50°C
Speaker Volume	Adjustable from 0 ~ 90dB at 1m (max)
Alarm time Range	Adjustable 3~30 s for alarm
Speaker Output	Chime/OFF/Alarm (Select by switch)
Mounting Brackets	Speaker, Reflector & Sensor brackets included

Dimensions

Sensor	71 x 60 x 30mm
Speaker	71 x 62 x 35mm
Reflector	60 x 51 x 8mm

