

# PSA Centrii

## CEN1KPWF

Access Control Keypad with Wi-Fi



### Features

- Up to 988 users
- IP66 weather resistant
- Multiple Access Modes: Smartphone, Card, PIN code, Fingerprint
- Remotely access & unlock via app
- Add/ Delete users by app
- Temporary Password (One-time Or Period Code)
- Metal housing, anti-vandal
- Programmable time restriction for users
- Support checking Opening Record
- 12~18VDC Power (power supply not supplied)
- Connects to 2.4GHz Wi-Fi band

### Specifications

<b>User Capacity</b>	Hardware User: 1000 / APP User: 500
<b>Common User</b>	100 Finger+ 888 PIN/Card Users
<b>Visitor User</b>	10
<b>Panic User</b>	2
<b>PIN Length</b>	4~6digits
<b>Operating Voltage</b>	12~18V DC (power supply not supplied)
<b>Idle Current</b>	<60mA
<b>Active Current</b>	< 150mA
<b>Proximity Card Reader</b>	EM and Mifare
<b>Wi-Fi Band</b>	2.4GHz only
<b>RFID Frequencies</b>	125kHz & 13.56MHz
<b>Read Range</b>	2~6cm
<b>Wiring Connections</b>	Relay output, exit button, alarm, door contact, Wiegand input/output
<b>Relay</b>	One (NO, NC, Common)
<b>Adjustable Relay Output Time</b>	0~99 Seconds (5 seconds default)
<b>Lock Output Load</b>	2 Amp Maximum
<b>Wiegand Interface</b>	EM card version: Wiegand 26~44 bits input & output (Factory default: Wiegand 26bits) Mifare card version:Wiegand 26~44 bits,56bits,58bits input & output (Factory default: Wiegand 34bits) 4 bits,8bits (ASCII), 10 digits Virtual Number(Factory default:4bits)
<b>Environment</b>	IP66
<b>Operating Temperature</b>	-30° C ~ 60° C (-22° F ~140° F)
<b>Operating Humidity</b>	0%RH~98%RH
<b>Physical</b>	Zinc-Alloy
<b>Color</b>	Sliver & Black
<b>Dimensions</b>	L148 x W43.5 x H22 (mm)
<b>Unit Weight</b>	330g
<b>Shipping Weight</b>	405g

Specifications may change without notice



### PSA Centrii App

Free app provided, support remote viewing on iOS or Android

