



# LIFESAVER

## PSA LIFESAVER 5000 Ionisation smoke alarm

- ✓ Sensitive to Fast Flaming Fires
- ✓ 240VAC with 9V battery backup

**PATENTED  
NEW QUICK  
SLIDE DESIGN**



### Features:

- ✓ Australian design and patented
- ✓ Hinge-less surface mount base plate
- ✓ Easier and quicker to fit and install
- ✓ Extra large cable terminals for easy installation
- ✓ Multiple fixing holes to suit junction boxes and knock out for conduit entry
- ✓ Suitable for ceiling or wall mount
- ✓ Extra large Test & Hush button for easy testing. Designed for easy reach with broom handle
- ✓ Australia's first alarm LED memory latch for 5 minutes after alarm to indicate "first to alarm" smoke alarm
- ✓ 4th terminal (9V) allows operation with fire indication panel to form part of an early warning indicator system

### Specifications:

Compatible with:	All PSA Lifesaver range of smoke alarms, heat alarm, strobe light and auxiliary devices, Remote test and hush plate and chip, Interconnect up to 24 units
Detection Method:	Dual Ionisation chamber
Alarm Sound:	85dB at 3 metres
Low Battery Indication:	Sounds a chirp at 30-40 second intervals, in addition to red LED indicator flashing
Alarm Duration:	As long as smoke is present, unit automatically resets when smoke clears
Alarm Indication:	Flashing red LED indicator red latching LED for 7 minutes on initiating smoke alarm
Compliance:	Activfire listed to AS3786:1993. Australian Standards Certified Product. Australian Electrical Authority Approval
Power Requirement:	240V AC 50Hz sine wave supply. Supplied with alkaline 9Vdc battery

FIRE • SECURITY • INTERCOMS



[psaproducts.com.au](http://psaproducts.com.au)

1300 772 776

[enquiry@psaproducts.com.au](mailto:enquiry@psaproducts.com.au)