

# **Echos**

## communicating colour



New Echos range models have been conceived in colour version, with 3.5" LCD screen, adjustable on horizontal axis for the best adaptability to avoid any light reflexes. Also this feature is very exploitable to properly adjust screen position according to the user tallness. Main feature of this monitor is its hand-free and open voice operation, no handset is

required. Frontal intuitive function-buttons: door lock release, auto switch-on, ring tone exclusion (with LED for setting indication), volume and picture brightness adjustment, intercommunication service and additional functions. Technology used is based on electronic call one for the best quality. It can be perfectly combined with Profilo and Matrix door stations and it's available in video kit version for one-way solutions.

#### Videointercom basis

EH9100CW screen | colour | colour | white and grey

Hand-free videointercom with adjustable 3.5" LCD screen. Supplied with buttons for open voice conversation On/Off, door lock release, ring tone exclusion (with LED for setting indication) and two buttons for additional services. User's interface has keys for audio volume and brightness adjustment.

#### Videointercom with 6 push buttons

EH9160CW screen | colour | colour | white and grey EH9160CT screen | colour | colour | metalized grey

Hand-free videointercom with adjustable 3.5" LCD screen. Supplied with buttons for open voice conversation On/Off, door lock release, ring tone exclusion (with LED for setting indication) and six buttons for intercommunicating service. User's interface shows keys for audio volume and brightness adjustment.



#### **BACK BOX**



built-in back box for EH9100CW, EH9160CW and EH9160CT. W x h x d + 192 x 92 x 46

#### WALL ADAPTORS



#### WA9100W

wall adaptor for surface mounting of EH9100CW and EH9160CW colour | white w x h x d  $\parallel$  196 x 90 x 26



#### WA9100T

wall adaptor for surface mounting of EH9160CT colour | metalized grey w x h x d | 196 x 90 x 26

### POWER SUPPLY

#### 1281

Stabilised power supply 230-127V ac, 48VA, outputs protected against overloading and short circuits, able to supply power to 1 camera unit and 2 FLAT or LCD video intercoms connected in parallel, or 1 camera unit and 1 video intercom (not FLAT). Output voltages: 13V ac and 21V dc. Certification: VDE. 8 A modules on DIN har.

#### TIMER

#### 1282E

Audio-Video timer. Allows operation in timer mode of a video system with electronic call, automatic deletion at the end of the conversation and the switching on of one video intercom at a time. Mountable on 6 A DIN module.



ACI srl Via E. Vanoni, 3 60027 Osimo (An) Italy

Tel (+39) 071.7202038° Fax (+39) 071.7202037

