



WI-FI ACCESS CONTROL KEYPAD

INT1KPWF



KEY FEATURES

- Up to 988 users
- IP66 weather resistant
- Multiple Access Modes: Smartphone, Card, PIN code, Fingerprint
- Remotely access & unlock via app
- Add/ Delete users by app
- Temporary Password (One-time Or Period Code)
- Metal housing, anti-vandal
- Programmable time restriction for users
- Support checking Opening Record
- 12-18VDC Power (*power supply not supplied*)
- Connects to 2.4GHz Wi-Fi band



IntelLink App

Free App provided, support remote viewing on iOS or Android™



FIRE • SECURITY • INTERCOMS

17 Millicent Street, Burwood, VIC 3125 Australia
Tel: 1300 PSA PRODUCTS (1300 772 776)
Fax: (03) 9888 9993
enquiry@psaproducts.com.au

psaproducts.com.au





| Model | INT1KPWF |
|------------------------------|--|
| User Capacity | Hardware User: 1000 / APP User: 500 |
| Common User | 100 Finger+ 888 PIN/Card Users |
| Visitor User | 10 |
| Panic User | 2 |
| PIN Length | 4-6digits |
| Operating Voltage | 12-18V DC (power supply not supplied) |
| Idle Current | <60mA |
| Active Current | < 150mA |
| Proximity Card Reader | EM and Mifare |
| Wi-Fi Band | 2.4GHz only |
| RFID Frequencies | 125kHz & 13.56MHz |
| Read Range | 2-6cm |
| Wiring Connections | Relay output, exit button, alarm, door contact, Wiegand input/output |
| Relay | One (NO, NC, Common) |
| Adjustable Relay Output Time | 0-99 Seconds (5 seconds default) |
| Lock Output Load | 2 Amp Maximum |
| Wiegand Interface | EM card version: Wiegand 26-44 bits input & output (Factory default: Wiegand 26bits) Mifare card version:Wiegand 26-44 bits,56bits,58bits input & output (Factory default: Wiegand 34bits) 4 bits,8bits (ASCII), 10 digits Virtual Number(Factory default:4bits) |
| Environment | Meets IP66 |
| Operating Temperature | -30° C ~ 60° C (-22° F -140° F) |
| Operating Humidity | 0%RH-98%RH |
| Physical | Zinc-Alloy |
| Color | Sliver & Black |
| Dimensions | L148 x W43.5 x H22 (mm) |
| Unit Weight | 330g |
| Shipping Weight | 405g |

FIRE • SECURITY • INTERCOMS