



HiLook
Powered by HIKVISION


4MP NETWORK DOME CAMERA

HLIPC-T240H / HLIPC-T240H-B (BLACK)



KEY FEATURES

- 1/3" progressive scan CMOS
- 2560 × 1440@20fps
- 2.8mm fixed lens
- H.265+, H.265, H.264+, H.264 compression
- Dual stream
- 120 dB WDR (Wide Dynamic Range)
- 3D DNR (Digital Noise Reduction)
- Up to 30 m IR range
- PoE (Power over Ethernet)
- IP 67



FIRE • SECURITY • INTERCOMS

17 Millicent Street, Burwood, VIC 3125 Australia
Tel: 1300 PSA PRODUCTS (1300 772 776)
Fax: (03) 9888 9993
enquiry@psaproducts.com.au psaproducts.com.au

PSA PSA Products
FIRE • SECURITY • INTERCOMS



SPECIFICATIONS

Model

HLIPC-T240H / HLIPC-T240H-B

Model		HLIPC-T240H / HLIPC-T240H-B
Camera	Image Sensor	1/3" progressive scan CMOS
	Min. Illumination	Color: 0.01 Lux @(F1.2, AGC ON), 0.028Lux @ (F2.0, AGC ON)
	Shutter Speed	1/3 s to 1/100,000 s
	Slow Shutter	Yes
	Auto-Iris	No
	Day & Night	IR cut filter
	DNR (Digital Noise Reduction)	3D DNR
	WDR (Wide Dynamic Range)	120 dB
	Angle Adjustment (Bracket)	Pan: 0° to 360°, tilt: 0° to 75°, rotation: 0° to 360°
Lens	Focal Length	2.8 mm
	Aperture	F2.0
	Focus	No
	FOV	2.8 mm, horizontal FOV 100°, vertical FOV 55°, diagonal FOV 117°
	Lens Mount	M12
IR	IR Range	Up to 30 m
	Wavelength	850 nm
Compression Standard	Video Compression	Main stream: H.265/H.264 Sub stream: H.265/H.264/MJPEG
	H.264 Type	Baseline Profile/Main Profile/High Profile
	H.264+	Main stream supports
	H.265 Type	Main Profile
	H.265+	Main stream supports
	Video Bit Rate	32 Kbps to 8 Mbps
Smart Feature-set	Region of Interest	1 fixed region for main stream and sub-stream
Image	Max. Resolution	2560 × 1440
	Main Stream Max. Frame Rate	50Hz: 20fps (2560 × 1440), 25fps (2304 × 1296, 1920 × 1080, 1280 × 720) 60Hz: 20fps (2560 × 1440), 30fps (2304 × 1296, 1920 × 1080, 1280 × 720)
	Sub-stream Max. Frame Rate	50Hz: 25fps (640 × 480, 640 × 360, 320 × 240) 60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)
	Image Enhancement	BLC, 3D DNR
	Image Settings	Saturation, brightness, contrast, sharpness, AGC, white balance adjustable by client software or web browser
	Day/Night Switch	Auto, scheduled




Model

HLIPC-T240H / HLIPC-T240H-B

Network	Network Storage	NAS (NFS, SMB/CIFS)
	Alarm Trigger	Motion detection, video tampering alarm, illegal login
	Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour
	General Function	Anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark, IP address filter
	Firmware Version	5.5.3
	API	ONVIF (PROFILE S, PROFILE G), ISAPI
	Simultaneous Live View	Up to 6 channels
	User/Host	Up to 32 users 3 levels: Administrator, Operator and User
	Client	iVMS-4200, Hik-Connect, iVMS-5200
	Web Browser	IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+
Interface	Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet port
General	Operating Conditions	-30 °C to 50 °C (-22 °F to 122 °F), humidity: 95% or less (non-condensing)
	Power Supply	12 VDC ± 25%, 5.5 mm coaxial power plug PoE (802.3af, class 3)
	Power Consumption and Current	12 VDC, 0.4 A, max: 5 W PoE: (802.3af, 36 V to 57 V), 0.2 A to 0.1 A, Max: 6.5 W
	Protection Level	IP67 TVS 2000V lightning protection, surge protection and voltage transient protection
	Material	Metal & Plastic
	Dimensions	Camera: Ø 110 mm × 93.2 mm (Ø 4.3" × 3.7") With package: 150 mm × 150 mm × 141 mm (5.9" × 5.9" × 5.6")
	Weight	Camera: approx. 350 g (0.8 lb.) With package: approx. 610 g (1.3 lb.)



DIMENSIONS



ACCESSORY



HLDS-1272ZJ-110
Wall Mounting Bracket



HLDS-1275ZJ
Vertical Pole Mounting Bracket



HLDS-1280ZJ-S
Junction Box



HLDS-1276ZJ
Corner Mounting Bracket

FIRE • SECURITY • INTERCOMS