



HiWatch series
Powered by HIKVISION

HIWATCH

HD 1080P EXIR TURRET CAMERA

PSAHIWC22



KEY FEATURES

- 2 megapixel high performance CMOS
- Analog HD output, up to 1080p resolution
- True Day/Night,
- Smart IR
- Up to 40m IR distance
- Switchable TVI/AHD/CVI/CVBS
- IP66

FIRE • SECURITY • INTERCOMS

17 Millicent Street, Burwood, VIC 3125 Australia
Tel: 1300 PSA PRODUCTS (1300 772 776)
Fax: (03) 9888 9993
enquiry@psaproducts.com.au psaproducts.com.au





Camera Specs	
Image Sensor	2 MP CMOS image sensor
Signal System	PAL/NTSC
Effective Pixels	1920 (H) × 1080 (V)
Min. illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter Time	1/25(1/30) s to 1/50,000 s
Lens	3.6mm (2.8 mm, 6 mm, 8 mm, 12 mm, 16 mm optional)
	Field of view: 103° (2.8 mm), 82.2°(3.6mm), 54°(6mm), 37.7°(8mm), 24.2°(12 mm), 18.8° (16 mm)
Lens Mount	M12
Day & Night	ICR
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 75°, Rotation: 0° to 360°
Synchronization	Internal synchronization
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 analog HD output
S/N Ratio	>62 dB
General	
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensation)
Power Supply	12 V DC±15%
Power Consumption	Max. 4 W
Protection Level	IP66
IR Range	Up to 40 m
Dimensions	Φ 126.7 mm × 97.84 mm (5" × 3.85")
Weight	350 g (0.77 lb.)

DIMENSION

